



MATERIAL SAFETY DATA SHEET
In Accordance with ISO/DIS 11014

Review Date 01/21/2020

Revision Date 01/20/2020

1 Identification of the Substance/Mixture and Company

Product Name: VIP Fixative®

MSDS Product Codes: 1060Z

Product Description: Acetic Zinc Formalin

Manufacturer:

Scigen Scientific Inc. 7031

Marcelle Street

Paramount CA 90723

USA 310-324-

6576

Emergency Telephone:

310-324-6576

Chemtrec

800-424-9300

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

2 Hazards Identification

Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Acute Tox. 5 H303 May be harmful if swallowed.

Acute Tox. 5 H333 May be harmful if inhaled.



Xn; Harmful

R20/21/22-40: Harmful by inhalation, in contact with skin and if swallowed. Limited evidence of a carcinogenic effect.



Xi; Sensitizing

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R43: May cause sensitisation by skin contact.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

Label elements

Labeling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

Code letter and hazard designation of product:

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]
In Accordance with ISO/DIS 11014

 Revision
Date

01/20/2020



Harmful

Hazard-determining components of labeling: formaldehyde

Risk phrases:

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

40 Limited evidence of a carcinogenic effect. 43

May cause sensitisation by skin contact.

Safety phrases:

2 Keep out of the reach of children.

36/37 Wear suitable protective clothing and gloves.

46 If swallowed, seek medical advice immediately and show this container or label.

56 Dispose of this material and its container to hazardous or special waste collection point.

Classification system:
NFPA ratings (scale 0 - 4)

Health = 2

Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4) Health

= 2

Fire = 0

Reactivity = 0

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable. **vPvB:** Not applicable.

3 Composition

Chemical characterization: Mixtures
Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

CAS: 50-00-0 EINECS: 200-001-8	formaldehyde Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Carc. 2, H351; Skin Corr. 1B, H314; Skin Sens. 1, H317	<5%
CAS: 67-56-1 EINECS: 200-659-6	methanol Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT SE 1, H370	<3%

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

4 First Aid Measures

Description of first aid measures General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. **After**

swallowing: Immediately call a doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed: No further relevant information available.

Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Firefighting Measures

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. **Special hazards arising from the substance or mixture:** No further relevant information available.

Advice for firefighters

Protective equipment: Mouth respiratory protective device.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Not required.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and Storage

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

Handling:

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed. **Specific**

end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

Additional information about design of technical systems: No further data; see item 7. **Control parameters**

Components with limit values that require monitoring at the workplace:

50-00-0 formaldehyde

PEL	Short-term value: 2 ppm Long-term value: 0.75 ppm see 29 CFR
REL	1910.1048(c) Short-term value: C 0.1* ppm
TLV	Long-term value: 0.016 ppm *15-min; See Pocket Guide App. A Short-term value: C 0.37 mg/m ³ , C 0.3 ppm
SEN	

67-56-1 methanol

PEL	260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls:

Personal protective equipment:

General protective and hygienic measures:

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative®

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands: Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Goggles recommended during refilling.

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]
In Accordance with ISO/DIS 11014

 Revision
Date

01/20/2020

9 Physical and Chemical Properties

Information on basic physical and chemical properties
General Information
Appearance

Form: Fluid
Color: Colorless
Odor: Pungent, makes eyes water **Odor threshold:** Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 100°C (212 °F)

Flash point: Not applicable.

Flammability (solid, gaseous): Not applicable.

Ignition temperature:

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined.
Upper: Not determined.

Vapor pressure at 20°C (68 °F): 23 hPa (17 mm Hg)

Density at 20°C (68 °F): 0.9875 g/cm³ (8.241 lbs/gal)

Relative density: Not determined. **Vapour density:** Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with

Water: Miscible

Segregation coefficient (n-octanol/water): Not determined.

Dynamic: Not determined. **Kinematic:** Not determined.

Other information: No further relevant information available.

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

10 Stability and Reactivity

Reactivity:

Chemical stability:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicology Information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

50-00-0 formaldehyde

Oral	LD50	>200 mg/kg (rat)
------	------	------------------

67-56-1 methanol

Oral	LD50	5628 mg/kg (rat)
------	------	------------------

Dermal	LD50	15800 mg/kg (rabbit)
--------	------	----------------------

Primary irritant effect:

On the skin: No irritant effect.

On the eye: No irritating effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

Carcinogenic categories

NTP (National Toxicology Program)

IARC (International Agency for Research on Cancer)

50-00-0	formaldehyde	1
---------	--------------	---

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

50-00-0	formaldehyde	R
---------	--------------	---

12 Ecological Information

Toxicity:

Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal Considerations

Recommendation: Use Neutralex[®] to detoxify formalin waste in accordance with Scigen's standard operating procedure.



Neutralex[®] treated waste is certified by California EPA and is approved for down the drain disposal world wide. Neutralex[®] treated formalin waste is classified as a nonhazardous material and meets guidelines for NPDES permits for all waste treatment facilities. Validation is confirmed by the Technology Certification seal shown to the left.

Uncleaned packagings: Dispose of as unused product.

14 Transport Information

UN-Number

DOT, ADR, ADN, IMDG, IATA

Void

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Void
Transport hazard class(es) DOT, ADR, ADN, IMDG, IATA Class	Void
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards Marine pollutant:	No
Special precautions for user:	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not applicable.
UN "Model Regulation":	-

15 Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture
SARA

Section 355 (extremely hazardous substances):	
50-00-0	formaldehyde
Section 313 (Specific toxic chemical listings):	
50-00-0	formaldehyde
67-56-1	methanol
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	

Proposition 65

Chemicals known to cause cancer:	
50-00-0	formaldehyde

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

Chemicals known to cause reproductive toxicity for females:
--

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020
Page

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories

EPA (Environmental Protection Agency)

50-00-0	formaldehyde		B1
---------	--------------	--	----

TLV (Threshold Limit Value established by ACGIH)

50-00-0	formaldehyde		A2
---------	--------------	--	----

NIOSH-Ca (National Institute for Occupational Safety and Health)

50-00-0	formaldehyde		
---------	--------------	--	--

OSHA-Ca (Occupational Safety & Health Administration)

50-00-0	formaldehyde		
---------	--------------	--	--

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative®

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

Hazard symbols:



Harmful

Hazard-determining components of labelling: formaldehyde

Risk phrases:

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

40 Limited evidence of a carcinogenic

effect. 43 May cause sensitisation by skin contact.

Safety phrases:

2 Keep out of the reach of children.

36/37 Wear suitable protective clothing and gloves.

46 If swallowed, seek medical advice immediately and show this container or label.

56 Dispose of this material and its container to hazardous or special waste collection point.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Page

MATERIAL SAFETY DATA SHEET

Product Name: VIP Fixative[®]

In Accordance with ISO/DIS 11014

Revision
Date

01/20/2020

Page

16 Other Information

This Material Safety Data Sheet has been furnished on request. A revised Material Safety Data Sheet will be furnished only if requested, also in case of specification changes. The above information, which is accurate to the best of our knowledge and belief, describes the safety aspects of our product but does not warrant any product properties. The company gives no warranty as to the accuracy or completeness of such information.